

**CAR STOPS: CS-70**

**IMPORTANT NOTE:** Car Stops are designed to be used on **EXPOSED RAILS** only; they cannot be modified for flush rail.

**FEATURES:**

- Fabricated from Carbon Steel
- Hinged-Type Double-ended
- Permanent Installation
- Can be Padlocked in Up or Down Position (Padlock not included)

MODEL #	HEIGHT (ABOVE RAILS)	RAIL SIZE	WEIGHT
CS-70L	15"	ASCE & ARA-A	135 lbs.
CS-70R	(381 mm)	90 - 141 lbs.	(61 kg) each



CS-70L and CS-70R

**CAR STOPS: CS-60**

**FEATURES:**

- Fabricated from Ductile Alloy
- Hinged-Type Single-ended
- Permanent Installation
- Can be Padlocked in Up or Down Position (Padlock not included)

MODEL #	HEIGHT (ABOVE RAILS)	RAIL SIZE	WEIGHT
CS-60L	15"	ASCE & ARA-A	91 lbs.
CS-60R	(381 mm)	90 - 141 lbs.	(41 kg) each



CS-60L and CS-60R

**CAR STOPS: CS-50**

**FEATURES:**

- Fabricated from Ductile Alloy
- Single-ended
- Easy Bolt and Clamp Installation
- No Drilling Required

MODEL #	HEIGHT (ABOVE RAILS)	RAIL SIZE	WEIGHT
CS-50	16-5/8" (422 mm)	4-1/2" to 7-7/16" 60 - 141 lbs.	135 lbs. (61 kg) each



CS-50

**CAR STOPS: CCS-2**

**FEATURES:**

- All-welded Steel Construction
- Cushioned Stops Transfer Impact Force to Tie and Ballast
- 4 Bolt Installation (per pair)
- No Holes to Drill

MODEL #	HEIGHT (ABOVE RAILS)	RAIL SIZE	WEIGHT
CCS-2	17" (432 mm)	4-1/2" to 7-7/16" 60 - 141 lbs.	180 lbs. (82 kg) each



CCS-2

**NOTE:** All Car Stops are sold per unit, but must be used in **PAIRS**.